

CARATTERISTICHE TECNICHE

TECHNICAL DATA

Modelli Models	KGS 125 BRICO	KGS 185 BRICO	KGS 220 BRICO	KGS 4SE	KGS 300E	KGS 400E	KGS 32-19	KGS 42-22	KGS 42-22 A	KGS 510S	KGS 515S	KGS 610S	KGS 630S	KGS 660S	KGS 660S EM6	KGS 700 ES
Lunghezza taglio orizzontale mm <i>Lenght of horizontal cut mm</i>	2500	3200	4220	4000	3200	4200	3200	4200	4200	4300	4300	5300	4300/ 5300	4300/ 5300	4300/ 5300	4100/ 5100
Altezza taglio verticale mm <i>Height of vertical cut mm</i>	1250	1850	2200	2200	1900	2200	1900	2200	2200	1950	2200	2200	2200	2200	2200	2100
Massima altezza taglio orizzontale mm <i>Max height of horizontal cut mm</i>	1250	1850	2200	1950	1650	1950	1650	1950	1950	1850	2100	2100	2100	2100	2100	2000
Massima altezza incisione verticale mm <i>Max height of vertical grooving mm</i>	1250	1850	2200	2200	1700	2000	1750	2050	2050	1950	2200	2200	2200	2200	2200	2100
Spessore di taglio mm <i>Depth of cut mm</i>	45	45	45	50	50	50	60	60	60	80	80	80	80	80	80	80
Potenza del motore HP <i>Motor HP</i>	3	3	3	4	4	4	4	4	4	6	6	6	6	6	6	6
Diametro lama principale mm <i>Diam. main saw blade mm</i>	250	250	250	250	250	250	250	250	250	300	300	300	300	300	300	300
Giri della lama principale mm <i>Circular saw speed U/ mm</i>	3100	3100	3100	5100	5100	5100	5100	5100	5100	5200	5200	5200	5200	5200	5200	5200
Diametro lama incisore mm <i>Diemeter scoring unit mm</i>	/	/	/	110#	110#	110#	110°	110°	110°	110°	110°	110°	110°	110°	110°	110°
Giri lama incisore U/min. <i>Circular scring blade U/min.</i>	/	/	/	7100	7100	7100	8000	8000	8000	7000	7000	7000	7000	7000	7000	7000
Peso lordo imballo telaio gabbie Kg <i>Gross weight frame with crates Kg</i>	190	220	250	370	412	520	420	528	576	520	570	750	820	820	820	850
Peso lordo imballo trave gabbie Kg <i>Gross weight beam with crates Kg</i>	90	100	110	290	298	320	414	436	450	435	450	450	510	580	590	790

N.B. altre capacità di taglio su richiesta
others possibilities of cut under request

